



## Packaging OpenTofu in pkgsrc

Leonardo Taccari

<leot@NetBSD.org>

The NetBSD Foundation

OpenTofu Day Europe 2026

March 23rd 2026

Amsterdam, Netherlands



# Outline

## Introduction

- NetBSD

- pkgsrc: the NetBSD package system

- pkgsrc build phases

- Why should we package OpenTofu and providers?

## Packaging

- Structure of pkgsrc package

- Go packaging

- Requirements of OpenTofu, Terraform and providers packaging

- A look to OpenTofu and providers in pkgsrc

## Testing migration from Terraform 0.12.x to OpenTofu 1.11.x

- Overview for update/migration

- Moto server-mode and Cram

- Cram tests to exercise Terraform/OpenTofu upgrades

## Conclusions

## References

# Introduction

## whoami (1)

- ▶ Cloud architect
- ▶ NetBSD {Developer,Director}
- ▶ I love to contribute to Open Source
- ▶ I write Infrastructure as Code using OpenTofu both for work and for fun!

## My adventure with OpenTofu I

- September 2020 ● Terraform v0.12.29 evaluation and introduction at work
- January 2021 ● Update of Terraform to v0.14.5 in pkgsrc-wip and several providers packaging
- March 2021 ● Proof of Concept of the pkgsrc Terraform/OpenTofu packaging infrastructure discussed in this talk
- October 2023 ● Packaging of OpenTofu v1.6.0-alpha2
- October 2023 ● Making terraform-provider-\* Terraform/OpenTofu agnostic

## My adventure with OpenTofu II

- January 2024 ● OpenTofu v1.6.0 released!
- July 2025 ● Master thesis on “[Stateful policies for static code analysis of Infrastructure as Code states](#)”
- September 2025 ● Packaging and **upgrade** testing of intermediate Terraform and OpenTofu releases
- March 2026 ● Request for comments and proposal to import OpenTofu packages and packaging infrastructure after pkgsrc-2026Q1 release

# NetBSD

- ▶ Free, fast, secure, and highly portable Unix-like open source operating system
- ▶ Started as a fork from 386BSD in 1993
- ▶ As an Operating System contains common Unix userland programs, compiler (GCC or clang), debugger, X11
- ▶ Other third-party software available via pkgsrc

## pkgsrc: the NetBSD package system

- ▶ Default package manager for NetBSD and SmartOS
- ▶ Started as a fork from FreeBSD ports in 1997
- ▶ Supports a lot of Unix-like operating systems including macOS, Linux, Solaris, FreeBSD, OpenBSD and more
- ▶ More than 29000 packages available
- ▶ Quarterly stable release (e.g. `pkgsrc-2026Q1`) and rolling release (`pkgsrc-current`)
- ▶ Written in make, shell scripting (sh, AWK) and C
- ▶ NetBSD bulk builders provides binary packages
- ▶ ... we will dig in building the packages from source in this talk!
- ▶ `pkgsrc-wip` (pkgsrc work in progress) is a project to get more people involved in pkgsrc

## pkgsrc build phases

When building a package there are several phases:

`fetch` fetch source code (also known as distfiles)

`patch` apply pkgsrc patches and possible user's patches

`build` configure and build the package

`package` create the binary package (.tgz archive)

`install` install the binary package

### Example

Install Go 1.26.x from source:

```
$ cd pkgsrc/lang/go126
```

```
$ make install
```

## Why should we package OpenTofu and providers?

- ▶ No binaries available for NetBSD
- ▶ Install/update like any other packages
- ▶ Be more in control of the software supply chain  
(see Terraform Registry's Terms of Service change in August 2023)

# Packaging

## Structure of pkgsrc package

- ▶ Each package lives in a dedicated directory `category/package` in the pkgsrc tree, e.g. `editors/neovim`
- ▶ Files under `category/package`:
  - `Makefile` main package logic, how to fetch/configure/build/install package, dependencies, adjust configure/build flags
  - `PLIST` list files that will be installed by the package
  - `distinfo` contains BLAKE2s/SHA512 checksums and file size for each distfile
  - `patches` contains possible pkgsrc patches
  - `DESCR` long description of the package
  - `ALTERNATIVES` provides alternatives, e.g. `tofu` defaults to `tofu111`

## Go packaging

- ▶ Go packages uses `lang/go/go-module.mk` logic
- ▶ Source code of the package and all its Go modules are the distfiles
- ▶ Modules are listed via `GO_MODULES_FILES` variable
- ▶ Build is done via `go install -v ${GOFLAGS} ${GO_BUILD_PATTERN}`
- ▶ `GOFLAGS` can be used to set extra flags, e.g. `-ldflags`
- ▶ `GO_BUILD_PATTERN` by default is `./...`
- ▶ Everything installed under `${GOPATH}/bin` will be installed

## Requirements of OpenTofu, Terraform and providers packaging

- ▶ Multiple Terraform and OpenTofu versions to support upgrade/migration
- ▶ Multiple major versions of providers when there are incompatibilities
- ▶ OpenTofu and Terraform are Go packages
- ▶ Providers are Go packages (gRPC servers not depending on OpenTofu)
- ▶ OpenTofu and Terraform should be able to pick pkgsrc installed providers out of the box
- ▶ Avoid boilerplate for packaging (`terraform/provider.mk` eases provider packaging)

# A look to OpenTofu and providers in pkgsrc I

## wip/opentofu111/Makefile

```
1 DISTNAME=      opentofu-1.11.5
2 PKGNAME=      ${DISTNAME:S/opentofu/&111/}
3 CATEGORIES=   net
4 MASTER_SITES= ${MASTER_SITE_GITHUB:=opentofu/}
5 GITHUB_PROJECT= opentofu
6 GITHUB_TAG=   v${PKGVERSION_NOREV}
7
8 MAINTAINER=   leot@NetBSD.org
9 HOMEPAGE=     https://opentofu.org/
10 COMMENT=     Open source infrastructure as code
11 LICENSE=     mpl-2.0
12
13 SUBST_CLASSES+= providers-prefix
14 SUBST_STAGE.providers-prefix= pre-configure
15 SUBST_MESSAGE.providers-prefix= Honor providers installed via pkgsrc
16 SUBST_FILES.providers-prefix= cmd/tofu/provider_source.go
17 SUBST_VARS.providers-prefix= PREFIX
18
19 do-install:
20     ${INSTALL_PROGRAM} ${WRKDIR}/.gopath/${GOPATH_BIN}/tofu ${DESTDIR}${PREFIX}/bin/tofu111
21
22     .include "go-modules.mk"
23
24     .include "../lang/go/go-module.mk"
25     .include "../mk/bsd.pkg.mk"
```

# A look to OpenTofu and providers in pkgsrc II

## wip/opentofu111/ALTERNATIVES

```
1 bin/tofu @PREFIX@/bin/tofu111
```

## wip/opentofu111/PLIST

```
1 @comment $NetBSD$  
2 bin/tofu111
```

## wip/opentofu111/patches/patch-provider\_\_source.go

```
1 $NetBSD$  
2  
3 Honors providers installed via pkgsrc.  
4  
5 --- cmd/tofu/provider_source.go.orig    2021-03-24 18:39:36.000000000 +0000  
6 +++ cmd/tofu/provider_source.go  
7 @@ -160,6 +160,9 @@ func implicitProviderSource(services *di  
8         addLocalDir(dir)  
9     }  
10  
11 +     // Providers installed via pkgsrc  
12 +     addLocalDir(filepath.Join("@PREFIX@", "share/terraform/plugins"))  
13 +  
14 +     // Anything we found in local directories above is excluded from being  
15 +     // looked up via the registry source we're about to construct.  
16 var directExcluded getproviders.MultiSourceMatchingPatterns
```

# A look to OpenTofu and providers in pkgsrc III

## wip/terraform-provider-random2/Makefile

```
1  DISTNAME=      terraform-provider-random-2.3.0
2  PKGNAME=      ${DISTNAME:S/terraform-provider-random/&2/}
3  CATEGORIES=   net
4  MASTER_SITES= ${MASTER_SITE_GITHUB:=hashicorp/}
5  GITHUB_PROJECT= terraform-provider-random
6  GITHUB_TAG=   v${PKGVERSION_NOREV}
7
8  MAINTAINER=   pkgsrc-users@NetBSD.org
9  HOMEPAGE=    https://www.terraform.io/docs/providers/random/
10 COMMENT=     Terraform provider for randomness
11 LICENSE=     mpl-2.0
12
13 # Previous net/terraform-provider-random (2.x) did not have any version suffix
14 SUPERSEDES+= terraform-provider-random-[0-9]*
15
16 TERRAFORM_PROVIDER_BIN=      terraform-provider-random
17 TERRAFORM_PROVIDER_NAMESPACE= hashicorp
18 TERRAFORM_PROVIDER_TYPE=     random
19
20 TERRAFORM_PROVIDER_LEGACY_INSTALL=      yes
21
22 .include "go-modules.mk"
23
24 .include "../..//lang/go/go-module.mk"
25 .include "../..//wip/terraform/provider.mk"
26 .include "../..//mk/bsd.pkg.mk"
```

## A look to OpenTofu and providers in pkgsrc IV

### wip/terraform-provider-random2/PLIST

```
1  @comment $NetBSD$
2  ${PLIST.legacy}bin/terraform-provider-${TERRAFORM_PROVIDER_TYPE}_v${TERRAFORM_PROVIDER_VERSION}
3  share/terraform/plugins/${OPENTOFU_PROVIDER_HOSTNAME}/${TERRAFORM_PROVIDER_NAMESPACE}/${
    TERRAFORM_PROVIDER_TYPE}/${TERRAFORM_PROVIDER_VERSION}/${GO_PLATFORM}/terraform-provider-${
    TERRAFORM_PROVIDER_TYPE}
4  share/terraform/plugins/${TERRAFORM_PROVIDER_HOSTNAME}/${TERRAFORM_PROVIDER_NAMESPACE}/${
    TERRAFORM_PROVIDER_TYPE}/${TERRAFORM_PROVIDER_VERSION}/${GO_PLATFORM}/terraform-provider-${
    TERRAFORM_PROVIDER_TYPE}
```

## Testing migration from Terraform 0.12.x to OpenTofu 1.11.x

## Overview for update/migration

- ▶ Shortest upgrade/migration path is: Terraform 0.12.x → Terraform 0.13.x → Terraform 0.14.x → Terraform 1.x → OpenTofu 1.6.x → OpenTofu 1.11.x
- ▶ It would be nice to not worry about cloud providers bill :)

## Moto server-mode and Cram

- ▶ **Moto** is a Python library to mock AWS Services
  - ▶ Its server-mode works well with OpenTofu and aws provider
- ▶ **Cram** is a functional testing framework for command line applications
  - ▶ It is like writing text snippets of interactive shell sessions

# Cram tests to exercise Terraform/OpenTofu upgrades I

requirements.t test to check installed Terraform/OpenTofu packages

```
1  #!/usr/bin/env cram
2
3  This test Terraform/OpenTofu upgrades in pkgsrc and goes from Terraform 0.12.x
4  to OpenTofu 1.11.x.
5
6  First we check that we have all needed Terraform versions...
7
8  We set CHECKPOINT_DISABLE variable because otherwise Terraform phones home and
9  check if there are new versions available via hashicorp/go-checkpoint:
10
11   $ export CHECKPOINT_DISABLE=yes
12
13  We check all Terraform versions:
14
15   $ terraform012 version
16   Terraform v0.12.* (glob)
17   $ terraform013 version
18   Terraform v0.13.* (glob)
19   $ terraform014 version
20   Terraform v0.14.* (glob)
21   $ terraform15 version
22   Terraform v1.5.* (glob)
23   on * (glob)
```

## Cram tests to exercise Terraform/OpenTofu upgrades II

requirements.t test to check installed Terraform/OpenTofu packages (cont.)

```
25 We also check that we have OpenTofu installed:
26
27 $ tofu16 version
28 OpenTofu v1.6.* (glob)
29 on * (glob)
30 $ tofu110 version
31 OpenTofu v1.10.* (glob)
32 on * (glob)
33 $ tofu111 version
34 OpenTofu v1.11.* (glob)
35 on * (glob)
```

### Example

Running Cram tests:

```
$ ./requirements.t
.
# Ran 1 tests, 0 skipped, 0 failed.
```

## Cram tests to exercise Terraform/OpenTofu upgrades III

### aws-vpc/versions.tf live module code

```
1 terraform {
2   required_version = ">= 0.12.31"
3
4   required_providers {
5     aws = ">= 3.28, <= 4"
6   }
7 }
```

### aws-vpc/main.tf live module code

```
1 provider "aws" {
2   access_key           = "test"
3   secret_key           = "test"
4   region               = "us-east-1"
5   skip_credentials_validation = true
6   skip_metadata_api_check   = true
7   skip_requesting_account_id = true
8
9   endpoints {
10    ec2 = "http://localhost:5000"
11    iam = "http://localhost:5000"
12  }
13 }
```

## Cram tests to exercise Terraform/OpenTofu upgrades IV

### aws-vpc/main.tf live module code (cont.)

```
15 module "vpc" {
16   source = "terraform-aws-modules/vpc/aws"
17   version = "3.7.0"
18
19   name = "testing-aws-vpc"
20   cidr = "10.0.0.0/16"
21
22   azs = ["us-east-1a", "us-east-1b", "us-east-1c"]
23   private_subnets = ["10.0.1.0/24", "10.0.2.0/24", "10.0.3.0/24"]
24   public_subnets = ["10.0.101.0/24", "10.0.102.0/24", "10.0.103.0/24"]
25
26   enable_dns_hostnames = true
27   enable_nat_gateway = true
28
29   tags = {
30     Terraform = "true"
31   }
32 }
```

# Cram tests to exercise Terraform/OpenTofu upgrades V

## upgrades-aws-vpc.t test to exercise upgrades

```
1  #!/usr/bin/env cram
2
3  This initialize and test the complete upgrade path from Terraform 0.12.x to
4  OpenTofu 1.11.x for aws-vpc module.
5
6  Enable job control and kill moto_server if tests are interrupted or exit for
7  any reasons.
8
9  $ set -m
10 $ trap 'echo cleanup &&; kill -9 %+ 2>/dev/null; trap -; wait' \
11 > ALRM EXIT HUP INT TERM
12
13 Start moto_server in the background:
14
15 $ moto_server 2>/dev/null &
16
17 Double-check that moto_server is running by checking its dashboard:
18
19 $ curl --fail --head --max-time 10 --no-show-headers \
20 > --retry-connrefused --retry 3 --silent \
21 > http://localhost:5000/moto-api/
22
23 Copy the entire module to a temporary directory so we do not need to worry and
24 clean .terraform and terraform.tfstate files:
25
26 $ cp -r "${TESTDIR}/aws-vpc" "${CRAMTMP}/aws-vpc"
27 $ cd "${CRAMTMP}/aws-vpc"
```

## Cram tests to exercise Terraform/OpenTofu upgrades VI

```
28
29 Set CHECKPOINT_DISABLE environment variable so Terraform does not phone home:
30
31   $ export CHECKPOINT_DISABLE=yes
32
33 Initialize the project with Terraform 0.12.x and create the resources:
34
35   $ terraform012 init >/dev/null
36   $ terraform012 plan -detailed-exitcode >/dev/null
37   [2]
38   $ terraform012 apply -auto-approve >/dev/null
39
40 Upgrade to Terraform 0.13.x by following
41 <https://developer.hashicorp.com/terraform/language/v1.1.x/upgrade-guides/0-13>...
42 We ensure that there are no pending changes to do:
43
44   $ terraform012 plan -detailed-exitcode >/dev/null
45
46 Run 0.13upgrade command so that provider requirements are rewritten to have
47 explicit source locations:
48
49   $ terraform013 0.13upgrade -yes >/dev/null
50
51 Rewrite providers in the state too and re-init:
52
53   $ terraform013 state replace-provider -auto-approve -- -/aws registry.terraform.io/hashicorp/aws >/dev
    /null
```

## Cram tests to exercise Terraform/OpenTofu upgrades VII

```
54 $ terraform013 state replace-provider -auto-approve -- -/random registry.terraform.io/hashicorp/random
    >/dev/null
55 $ terraform013 init >/dev/null
56
57 Run apply to complete the upgrade
58
59 $ terraform013 apply -auto-approve >/dev/null
60
61 Upgrade to Terraform 0.14.x by following
62 <https://developer.hashicorp.com/terraform/language/v1.1.x/upgrade-guides/0-14>...
63 We ensure that there are no pending changes to do:
64
65 $ terraform013 plan -detailed-exitcode >/dev/null
66
67 Rewrite providers in the state too and re-init:
68
69 $ terraform014 init >/dev/null
70
71 Run apply to complete the upgrade
72
73 $ terraform014 apply -auto-approve >/dev/null
74
75 Upgrade to Terraform 1.5 by following
76 <https://developer.hashicorp.com/terraform/language/v1.5/upgrade-guides/>...
77 We ensure that there are no pending changes to do:
78
79 $ terraform014 plan -detailed-exitcode >/dev/null
80
```

## Cram tests to exercise Terraform/OpenTofu upgrades VIII

```
81 Rewrite providers in the state too and re-init:
82
83   $ terraform15 init >/dev/null
84
85 Run apply to complete the upgrade
86
87   $ terraform15 apply -auto-approve >/dev/null
88
89 Upgrade to OpenTofu 1.6 by following
90 <https://opentofu.org/docs/intro/migration/migration-guide/>...
91 We ensure that there are no pending changes to do:
92
93   $ terraform15 plan -detailed-exitcode >/dev/null
94
95 Re-init:
96
97   $ tofu16 init >/dev/null
98
99 Run apply to complete the upgrade:
100
101   $ tofu16 apply -auto-approve >/dev/null
102
103 Upgrade to OpenTofu 1.10 by following
104 <https://opentofu.org/docs/intro/migration/migration-guide/>...
105 We ensure that there are no pending changes to do:
106
107   $ tofu16 plan -detailed-exitcode >/dev/null
108
```

## Cram tests to exercise Terraform/OpenTofu upgrades IX

```
109 Re-init:
110
111   $ tofu110 init >/dev/null
112
113 Run apply to complete the upgrade:
114
115   $ tofu110 apply -auto-approve >/dev/null
116
117 Upgrade to OpenTofu 1.11 by following
118 <https://opentofu.org/docs/intro/migration/migration-guide/>...
119 We ensure that there are no pending changes to do:
120
121   $ tofu110 plan -detailed-exitcode >/dev/null
122
123 Re-init:
124
125   $ tofu111 init >/dev/null
126
127 Run apply to complete the upgrade:
128
129   $ tofu111 apply -auto-approve >/dev/null
130
131 Stop moto_server and restore to default trap handlers:
132
133   $ kill %+
134   $ trap -
```

# Thanks

- ▶ Thanks to Benny Siegert and Taylor R Campbell!

## Conclusions

- ▶ We have introduced NetBSD and pkgsrc
- ▶ We have seen how to package Terraform/OpenTofu and providers in pkgsrc
- ▶ We have seen how a complete migration path from Terraform 0.12.x to OpenTofu 1.11.x can be tested via `moto_server` and Cram
- ▶ All this work should be available in pkgsrc-2026Q2!

## References I

Alistair Crooks, Hubert Feyrer, The pkgsrc Developers.

The pkgsrc guide.

<https://www.NetBSD.org/docs/pkgsrc/>.

OpenTofu.

Opentofu.

<https://opentofu.org/>.

HashiCorp.

Terms of use - terraform registry.

<https://registry.terraform.io/terms>.

Steve Pulec.

Moto - mock aws services.

<https://github.com/getmoto/moto>.

## References II

bitheap.

Cram: It's test time.

<https://bitheap.org/cram/>.

Leonardo Taccari.

Updating terraform/opentofu packages and providers: request for review and testing.

<https://mail-index.NetBSD.org/tech-pkg/2026/03/04/msg032042.html>.



Thanks!

# Questions?



OpenTofu Day  
EUROPE



<https://sched.co/2DY5x>

: Leonardo Taccari

: [leot@NetBSD.org](mailto:leot@NetBSD.org)

: [@iamleot@mastodon.sdf.org](https://mstdn.org/@iamleot)

Extra

## wip/terraform/provider.mk

```
1 # $NetBSD$
2 #
3 # This file implements common logic for Terraform providers in pkgsrc.
4 #
5 # Package-settable variables:
6 #
7 # TERRAFORM_PROVIDER_HOSTNAME (optional)
8 #     Hostname of the Terraform registry that distributes the provider.
9 #
10 #     Default: registry.terraform.io
11 #
12 # OPENTOFU_PROVIDER_HOSTNAME (optional)
13 #     Hostname of the OpenTofu registry that distributes the provider.
14 #
15 #     Default: registry.opentofu.org
16 #
17 # TERRAFORM_PROVIDER_BIN
18 #     Binary name of the provider that will be installed under
19 #     TERRAFORM_PROVIDER_DIR.
20 #
21 # TERRAFORM_PROVIDER_NAMESPACE
22 #     Organizational namespace within the Terraform registry.
23 #
24 # TERRAFORM_PROVIDER_TYPE
25 #     Short name for the platform or system the provider manages.
```

## terraform/provider.mk II

```
26 #
27 # TERRAFORM_PROVIDER_VERSION (optional)
28 #   Version of the provider.
29 #
30 #   Default: ${PKGVERSION_NOREV}
31 #
32 # TERRAFORM_PROVIDER_DIR (optional)
33 #   Directory where the provider will be installed.
34 #
35 #   Default: share/terraform/plugins/${TERRAFORM_PROVIDER_HOSTNAME}/${TERRAFORM_PROVIDER_NAMESPACE}/
36 #           ${TERRAFORM_PROVIDER_TYPE}/${TERRAFORM_PROVIDER_VERSION}/${GO_PLATFORM}
37 #
38 # OPENTOFU_PROVIDER_DIR (optional)
39 #   Directory where the provider will be installed.
40 #
41 #   Default: share/terraform/plugins/${OPENTOFU_PROVIDER_HOSTNAME}/${TERRAFORM_PROVIDER_NAMESPACE}/${
42 #           ${TERRAFORM_PROVIDER_TYPE}/${TERRAFORM_PROVIDER_VERSION}/${GO_PLATFORM}
43 #
44 # TERRAFORM_PROVIDER_LEGACY_INSTALL (optional)
45 #   Install the provider under ${PREFIX}/bin too so that can be used by
46 #   Terraform 0.12.x.
47 #
48 #   Default: no
49 #
50 # Keywords: opentofu terraform
51 #
52 TERRAFORM_PROVIDER_HOSTNAME?= registry.terraform.io
```

## terraform/provider.mk III

```
52 TERRAFORM_PROVIDER_VERSION?=      ${PKGVERSION_NOREV}
53 TERRAFORM_PROVIDER_DIR?=          share/terraform/plugins/${TERRAFORM_PROVIDER_HOSTNAME}/${
    TERRAFORM_PROVIDER_NAMESPACE}/${TERRAFORM_PROVIDER_TYPE}/${TERRAFORM_PROVIDER_VERSION}/${
    GO_PLATFORM}
54
55 OPENTOFU_PROVIDER_HOSTNAME?=      registry.opentofu.org
56 OPENTOFU_PROVIDER_DIR?=          share/terraform/plugins/${OPENTOFU_PROVIDER_HOSTNAME}/${
    TERRAFORM_PROVIDER_NAMESPACE}/${TERRAFORM_PROVIDER_TYPE}/${TERRAFORM_PROVIDER_VERSION}/${
    GO_PLATFORM}
57
58 TERRAFORM_PROVIDER_LEGACY_INSTALL?=  no
59
60 PLIST_SUBST+=                     TERRAFORM_PROVIDER_HOSTNAME=${TERRAFORM_PROVIDER_HOSTNAME}
61 PLIST_SUBST+=                     TERRAFORM_PROVIDER_NAMESPACE=${TERRAFORM_PROVIDER_NAMESPACE}
62 PLIST_SUBST+=                     TERRAFORM_PROVIDER_TYPE=${TERRAFORM_PROVIDER_TYPE}
63 PLIST_SUBST+=                     TERRAFORM_PROVIDER_VERSION=${TERRAFORM_PROVIDER_VERSION}
64
65 PLIST_SUBST+=                     OPENTOFU_PROVIDER_HOSTNAME=${OPENTOFU_PROVIDER_HOSTNAME}
66
67 PRINT_PLIST_AWK+=                 { sub("${TERRAFORM_PROVIDER_HOSTNAME}", "${TERRAFORM_PROVIDER_HOSTNAME}") }
68 PRINT_PLIST_AWK+=                 { sub("${TERRAFORM_PROVIDER_NAMESPACE}", "${TERRAFORM_PROVIDER_NAMESPACE}") }
69 PRINT_PLIST_AWK+=                 { gsub("${TERRAFORM_PROVIDER_TYPE}", "${TERRAFORM_PROVIDER_TYPE}") }
70 PRINT_PLIST_AWK+=                 { sub("${TERRAFORM_PROVIDER_VERSION}", "${TERRAFORM_PROVIDER_VERSION}") }
71
72 PRINT_PLIST_AWK+=                 { sub("${OPENTOFU_PROVIDER_HOSTNAME}", "${OPENTOFU_PROVIDER_HOSTNAME}") }
73
74 PRINT_PLIST_AWK+=                 /bin/ { sub("^", "${PLIST.legacy}") }
```

## terraform/provider.mk IV

```
76 PLIST_VARS+=      legacy
77 .if ${TERRAFORM_PROVIDER_LEGACY_INSTALL:t1} == "yes"
78 PLIST.legacy=     yes
79 .endif
80
81 INSTALLATION_DIRS+=      ${TERRAFORM_PROVIDER_DIR}
82 INSTALLATION_DIRS+=      ${OPENTOFU_PROVIDER_DIR}
83 .if ${TERRAFORM_PROVIDER_LEGACY_INSTALL:t1} == "yes"
84 INSTALLATION_DIRS+=      bin
85 .endif
86
87
88 #
89 # This should be overwritten via 'do-install:' target, however
90 # lang/go/go-{module,package}.mk already overwrite them.
91 #
92 .if !target(pre-install)
93 pre-install:
94     ${RUN} \
95     if [ -f ${WRKDIR}/.gopath/bin/${TERRAFORM_PROVIDER_BIN} ]; then \
96         ${INSTALL_PROGRAM} ${WRKDIR}/.gopath/bin/${TERRAFORM_PROVIDER_BIN} \
97             ${DESTDIR}${PREFIX}/${TERRAFORM_PROVIDER_DIR} ; \
98         ${LN} -sf ${PREFIX}/${TERRAFORM_PROVIDER_DIR}/${TERRAFORM_PROVIDER_BIN} \
99             ${DESTDIR}${PREFIX}/${OPENTOFU_PROVIDER_DIR}/${TERRAFORM_PROVIDER_BIN} ; \
100         { [ -d ${WRKDIR}/.gopath ] && chmod -R +w ${WRKDIR}/.gopath || ${TRUE} ; } ; \
101         ${RM} -rf ${WRKDIR}/.gopath/bin ; \
102     elif [ -f ${WRKDIR}/bin/${TERRAFORM_PROVIDER_BIN} ]; then \
103         ${INSTALL_PROGRAM} ${WRKDIR}/bin/${TERRAFORM_PROVIDER_BIN} \
```

## terraform/provider.mk V

```
104         ${DESTDIR}${PREFIX}/${TERRAFORM_PROVIDER_DIR} ; \
105     ${LN} -sf ${PREFIX}/${TERRAFORM_PROVIDER_DIR}/${TERRAFORM_PROVIDER_BIN} \
106         ${DESTDIR}${PREFIX}/${OPENTOFU_PROVIDER_DIR}/${TERRAFORM_PROVIDER_BIN} ; \
107     ${RM} -rf ${WRKDIR}/bin ; \
108     ${RM} -rf ${WRKDIR}/pkg ; \
109     fi
110 .   if ${TERRAFORM_PROVIDER_LEGACY_INSTALL:t1} == "yes"
111     ${LN} -sf ${PREFIX}/${TERRAFORM_PROVIDER_DIR}/${TERRAFORM_PROVIDER_BIN} \
112         ${DESTDIR}${PREFIX}/bin/${TERRAFORM_PROVIDER_BIN}_v${TERRAFORM_PROVIDER_VERSION} ;
113 .   endif
114 .endif
```